

Multi-Channel Safety Tester/Hipot Tester

ES9005-150-8 Scanning 8-channel

Features

- ES9005-150-8:8-channel scanning AC/DC withstanding voltage & insulation tester
- 240×64 Dot-matrix graphic LCD display
- Fast discharge and arc detection function
- Body protection function
- Built-in 8-channel matrix scanner for convenient use
- Set voltage rising time, test time, and voltage dropping time randomly for different load, DC withstanding voltage current judging & waiting time
- 100 test steps being stored per group, totally 50 groups, and the total testing steps are limited at 500
- Current base number correction function
- Brand new operation interface and humanized panel design
- Abundant interfaces Handler, RS-232C, SCAN, GPIB(optional)

Brief Introduction

- AC/DC withstanding voltage & insulation tester is a kind of Hipot Tester. Due to simple and compact structure, mature technique, brand new structure and operating interface, the operation becomes more convenient, and more practical functions are included as well. ES9005-150-8 can be widely applied in transformer, device, component especially for winding safety inspection.



ES9005-150-8



Specifications

Model		ES9005-150-8	
Withstanding voltage test			
Output voltage	AC	0.05kV—5kV $\pm(1.0\%$ of reading+5 digit) (50、60Hz optional)	
	DC	0.05kV—6kV $\pm(1.0\%$ of reading+5 digit)	
	Voltage adjustment rate	$\leq(1.0\% +10V)$ (rated power)	
Current test range	AC	0.01mA - 30mA	
	DC	0.1 μ A - 10mA	
	Test accuracy	$\pm(1.0\%$ of reading+5 digit)	
	Discharge function	Discharge after test ends (DCW)	
Insulation resistance test			
Output voltage		0.05kV – 1kV $\pm(1.5\%$ of reading+5V)	
Resistance test range		0.1M Ω –10G Ω , (Current range within 10nA-10mA)	
Resistance test	500V-1000V	1M Ω – 1G Ω $\pm(5\%$ of reading +5 digit) 1G Ω – 10G Ω $\pm(10\%$ of reading +5 digit)	
accuracy	50V-500V	0.1M Ω – 1G Ω $\pm(10\%$ of reading +5 digit)	
Discharge function		Discharge after test ends	
Arc detection			
Measurement range	AC	1mA - 15mA	
	DC	1mA - 10mA	
General specification			
Memory		50groups, 100 steps per group, totally 500 steps	
Voltage rise-time		0.1s - 999s	
Voltage fall-time		0.1s - 999s	
Voltage wait-time		0.1s - 99.9s (only for DC)	
Test time setting		0.3s - 999s	
Interface			
Standard		RS232, USB,HANDLER, REMOTE I/O , SCAN	
Options		GPIB	